

Mojave Series 550T and 550AT Thermal Door Quote/Order Request Form

NOTE: PLEASE DOWNLOAD FORM TO SUBMIT. DO NOT FILL FORM ONLINE.

Email completed form to usalum@crlaurence.com.

Fax checklist to U.S. Aluminum Technical Sales at (877) 883-7547

To review call (800) 627-6440. This form is available online at usalum.com.

Page 1 of 2 COMPANY NAME _____ PHONE ACCOUNT NO. FAX CONTACT JOB NAME EMAIL **DOOR SWING CHART** □ ORDER P.O. # ■ QUOTE DATE INTERIOR STANDARD PROFILE DIMENSIONS THICKNESS STILE **TOP RAIL BOTTOM RAIL** 550T WIDE STILE THERMAL DOOR 7-1/4" 1-3/4" 5-1/2" EXTERI 1-3/4" 7-1/4" (Foam Filled) 550AT WIDE STILE ADVANCE THERMAL DOOR 5-1/2" (Foam Filled) 6" (Foam Filled) Use the Door Swing Chart to determine OPTIONAL how the door(s) should be handed. **APPLICATION: HEAVY TRAFFIC** DOOR STILE APPLICATION GLASS STOP **LOCKING OPTIONS** 1" (25 mm) Square Glass Stops MS Hookbolt With Two Cylinders - STD ☐ 550T Wide Stile Thermal Door ■ Long Throw Deadlock With Cylinders ☐ 550AT Wide Stile Advance Thermal Door ☐ 3-Point Locking @ Pair With Cylinders **TOP RAIL - INCLUDES GLASS STOP** ■ Latch/Deadlock (DH189) With Cylinders □ 6" WT201 (Standard) ☐ Thumbturn in Lieu of Cylinder **DOOR FINISH** □ 2-7/8" ☐ Latchlock (DH002) HT201 □ 11 - Clear Anodized Class I ☐ Cylinder (Ext.) ☐ Cylinder (Int.) **4-5/16** HT101 □ 22 - Dark Bronze / Black Anodized Class I ☐ Thumbturn (Int.) □ Custom ☐ 52 - Bone White 70% KYNAR® (2-Coat) Lock Indicator ☐ 71 - Standard 70% KYNAR® (2-Coat) Cylinder Guard Standard Color per Chart- Specify **BOTTOM RAIL - INCLUDES GLASS STOP** ☐ Flushbolts (DH008) 7-1/4" JT650 (Standard) □ Paddle Handle ☐ 71 - Custom 70% KYNAR® (2-Coat) - Specify DH569 Lever Handle **4-5/16** HT101 □ Interior □ Back to Back **□** 6" WT201 • CRL DL2150 Lever Handle ☐ 71 - Custom 70%KYNAR®(3-Coat) - Specify **10**" WT196 □ Interior □ Back to Back □ Electric Strike **MUNTINS - INCLUDES GLASS STOP** □ Prep and Supply □ Prep Only **3-5/8** (HT202) PANIC DEVICES □ 5-1/16" (MT101) ☐ Jackson 1285 Concealed Vertical Rod Panic □ 6-3/4" (MT201) **DOOR HINGING** ☐ Jackson 1295 Rim Panic Device □ 8" (JT650) ☐ Top/Bottom and Intermediate Offset Pivots ☐ Jackson 2086 Concealed Vertical Rod Panic (OP500/DH010) □ 10-3/4" (MT196) ☐ Jackson 2095 Rim Panic Device Additional Pivot

DH010 ☐ Jackson 1085 Concealed Vertical Rod Panic ____ per Door HARDWARE FINISH DOOR FINISH ☐ Jackson 1095 Rim Panic Device ☐ 1-1/2 Pair Butt Hinges (DH009) Clear 11, 12, 52, 71 ☐ Adams-Rite 8400 Mortise Panic Device ■ Additional Butt Hinge Bronze ☐ Adams-Rite 8600 Concealed Vertical Rod Panic Add _____ per Door
☐ Continuous Geared Hinge (DH492) Specify ☐ Adams-Rite 8800 Rim Panic Device ■ By USALUM □ with cylinder □ cylinder by others (prep only) By Customer ☐ Von Duprin[®] 33AE ☐ Von Duprin[®] 35AE □ Prep and Supply ☐ Von Duprin[®] 3327AE ☐ Von Duprin[®] 3527AE DOOR SWEEP ☐ Prep Only (Selection Above) ☐ Von Duprin[®] 3347AE ☐ Von Duprin[®] 3547AE ☐ Yes ☐ No ■ No Prep • Outside Von Duprin Trim Exposed Fasteners □ 360L □ 360T □ 388NL □ Concealed Fasteners with cylindercylinder by others (prep only) ■ Exit Only DOOR SWING **DOOR OPENING SIZE** QTY □ By USALUM □ By Customer ■ LHR Hinge Left Swing Out □ 36" x 84" ea. □ Prep and Supply ☐ RHR Hinge Right Swing Out ea. Custom Single ___ □ Prep Only (Selection Above) ☐ LH Hinge Left Swing In ea. Door Tag # __ ☐ RH Hinge Right Swing In ea. FOR OFFICE USE ONLY □ 72" x 84" □ PAIR Swing In ea. Custom Pair ___ ■ PAIR Swing Out TAKEN BY: Door Tag # ___

Maximum Leaf Size 48" x 96"

PRICED BY:

EDITED BY:



Mojave Series 550T and 550AT Thermal Door Quote/Order Request Form

NOTE: PLEASE DOWNLOAD FORM TO SUBMIT. DO NOT FILL FORM ONLINE.

Email completed form to usalum@crlaurence.com.

Fax checklist to U.S. Aluminum Technical Sales at (877) 883-7547

To review call (800) 627-6440. This form is available online at usalum.com.

Page 2 of 2

		raye 2 01 2
PUSH/PULL HARDWARE	DOOR CLOSER	FRAME SYSTEM
☐ Standard Push/Pull	☐ O.H. Concealed (Offset-Prep Only)	Series IT451 2" x 4-1/2" ☐ Open Back
☐ Offset Pulls	 Standard Jackson Closer (Supply) 	Subframe ☐ 1" x 4-1/2" (Thermal) Tubular Only
☐ None	□ 90° □ 105° Hold Open □ Yes □ No	
☐ Custom ☐ By USALUM ☐ By Customer	 CRL Surface Mount Closer (Supply) 	
☐ Prep and Supply ☐ Prep Only	☐ Drop Plate	FRAME TYPE
NOTE: Prep Only Requires Manufacturer's	☐ Door Stop/Holder Degree	☐ Up and Over (No Transom)
Name , Model, and Template	□ No Closer Required	☐ 126" (3.2 m) High With Transom☐ Frame Only
Manufacturer:	☐ Custom ☐ By USALUM ☐ By Customer	☐ Door Only (No Frame)
Model:	☐ Prep and Supply ☐ Prep Only	□ Custom
	NOTE: Prep Only Requires Manufacturer's Name,	
	Model, and Template	
SLUMCRAFT PANIC DEVICES	Manufacturer:	CLEARANCES/THRESHOLD
□ PA100 □ PA110	Model:	
Blumcraft Electric Strike		Clearance from Bottom of Door to Finish Floor
YES ☐ Folger Adam 310-1 with 3/4"		□ 11/16" Standard (Required for 0P500 Pivot Set)
Straight Keeper (FA3101-24V DC) NO □ Without Signal Switch		☐ Custom Clearance
Furnish by CRL		Specify
Exterior Blumcraft Pull		. ,
□ D □ F □ J-S □ L-S □ Z(None)		TT245 1/2" Threshold
• Exterior Blumcraft Cylinder		
Exterior Key CylinderNo Exterior Key Cylinder		
Blumcraft Hardware Finishes		
☐ Stainless Steel		
☐ #4 Satin ☐ #8 Polish		
☐ Brass ☐ #4 Satin ☐ #8 Polish		
☐ #4 Satin ☐ #8 Polish		

A	ADDITIONAL NOTES OR SKETCHES
	FOR OFFICE HOE ONLY
	FOR OFFICE USE ONLY
	TAKEN BY:
	IARCH DI.
	PRICED BY:
APPROVED BY	DATE
	NOTE: PLEASE DOWNLOAD FORM TO SUBMIT. DO NOT FILL FORM ONLINE.

NOTE: PLEASE DOWNLOAD FORM TO SUBMIT. DO NOT FILL FORM ONLINE.

Email completed form to usalum@crlaurence.com.

Fax checklist to U.S. Aluminum Technical Sales at (877) 883-7547

To review call (800) 627-6440. This form is available online at usalum.com.