Custom Series 650-T, 700-T, and 750-T Thermal Door Quote/Order Request Form

Fax Completed Checklist to U.S. Aluminum Technical Sales at (866) 262-3299. Then call to discuss: (800) 262-5151 (U.S.), (877) 421-6144 (Canada), or (323) 588-1281 (International). Ask for Extension 15305. This form is also available online at **usalum.com**.

COMPANY NAME _____ **PHONE** _____

CONTACT _____ **ACCOUNT NO.** _____ **FAX** _____

JOB NAME _____ **EMAIL** _____

❑ **QUOTE** ❑ **ORDER P.O. #** _____ **DATE** _____

SERIES	THICKNESS	STANDARD PROFILE DIMENSIONS STILE	TOP RAIL	BOTTOM RAIL
NARROW STILE	2-1/4"	3-1/4"	2-1/2"	3-7/8"
MEDIUM STILE	2-1/4"	3-1/2"	3-1/2"	6-1/2"
WIDE STILE	2-1/4	4-1/4"	4-1/4"	6-1/2"

DOOR SWING CHART



Use the Door Swing Chart to determine how the door(s) should be handed.

DOOR STILE / APPLICATION

Thermal Entrance
- ❑ 650-T Narrow — Light to Moderate Traffic
- ❑ 700-T Medium — Moderate to Heavy Traffic
- ❑ 750-T Wide — Heavy Traffic

DOOR HINGING

- ❑ Top/Bottom and Intermediate Offset Pivots
- ❑ Additional Pivot
  Add _____ per Door
- ❑ 1-1/2 Pair Butt Hinges
- ❑ Additional Butt Hinge
  Add _____ per Door
- ❑ Continuous Geared Hinge
- ❑ Custom ❑ By USALUM ❑ By Customer
- ❑ Prep and Supply ❑ Prep Only

NOTE: Prep Only Requires Manufacturer's Name , Model, and Template

Manufacturer: _____

Model: _____

_____

DOOR OPENING SIZE

- ❑ 36" x 84"
- ❑ Custom Single _____
  Door Tag # _____
- ❑ 72" x 84"
- ❑ Custom Pair _____
  Door Tag # _____

DOOR SWING / QTY

- ❑ LHR Hinge Left Swing Out _____ ea.
- ❑ RHR Hinge Right Swing Out _____ ea.
- ❑ LH Hinge Left Swing In _____ ea.
- ❑ RH Hinge Right Swing In _____ ea.
- ❑ PAIR Swing In _____ ea.
- ❑ PAIR Swing Out _____ ea.

TOP RAIL

- ❑ Standard
- ❑ 2-1/2"
- ❑ 3-1/2"
- ❑ 4-1/4"
- ❑ Custom _____

LOCKING OPTIONS

- ❑ MS Dead Lock With Two Cylinders - **STD**
- ❑ MS Bottom Rail Lock With Cylinders
- ❑ Latch Set - DH002
- ❑ Latch Set/Dead Bolt DH189
- ❑ 3-PT. Lock Pairs With Cylinders
- ❑ Cylinder Thumbturn (INT)
- ❑ T-Turn in Lieu of (1) Cylinder
- ❑ Elect Strike
- ❑ Power Transfer
- ❑ Jax 1085 CVR Panic Device Exit Only (Available for Series 700-T and 750-T only)
- ❑ Jax 1285 CVR Panic Device Exit Only (Available for Series 700-T and 750-T only)
- ❑ Jackson 2086 CVR Panic Device Exit Only (Available for Series 700T and 750T only)
- ❑ Jax 1095 Rim Panic Device
  ❑ w/CYL. ❑ Exit Only
- ❑ Jax 1295 Rim Panic Device (Available for Series 700-T and 750-T only)
  ❑ w/CYL. ❑ Exit Only
- ❑ Jax 2095 Rim Panic Device (Available for Series 700-T and 750-T only)
  ❑ w/CYL. ❑ Exit Only
- ❑ AR 8400 Mortise Panic Device
  ❑ w/CYL. ❑ Exit Only
- ❑ AR 8800 Rim Panic Device
  ❑ w/CYL. ❑ Exit Only
- ❑ AR 8600 CVR Panic Device
  ❑ w/CYL. ❑ Exit Only
- ❑ Custom ❑ By USALUM ❑ By Customer
- ❑ Prep and Supply ❑ Prep Only

NOTE: Prep Only Requires Manufacturer's Name , Model, and Template

Manufacturer: _____

Model: _____

_____

BOTTOM RAIL

- ❑ Standard
- ❑ 3-7/8"
- ❑ 6-1/2"
- ❑ 6-1/2"
- ❑ 10"
- ❑ Custom _____

PUSH/PULL HARDWARE

- ❑ Standard Push/Pull
- ❑ Offset Pulls
- ❑ None _____
- ❑ Custom ❑ By USALUM ❑ By Customer
- ❑ Prep and Supply ❑ Prep Only

NOTE: Prep Only Requires Manufacturer's Name , Model, and Template

Manufacturer: _____

Model: _____

_____

*MID-PANEL (MUNTIN)

- ❑ 2-1/2" ❑ Custom
- ❑ 6" _____

DOOR FINISH

- ❑ 11 - Clear Anodized
- ❑ 22 - Dark Bronze Anodized
- ❑ 33 - Black Anodized
- ❑ 52 - Bone White 70% KYNAR® (2-Coat)
- ❑ 71 - Standard 70% KYNAR® (2-Coat)
  Standard Color per Chart - Specify

_____

- ❑ 71 - Custom 70% KYNAR® (2-Coat) - Specify

_____

- ❑ 71 - Custom 70%KYNAR®(3-Coat) - Specify

_____

HARDWARE FINISH / DOOR FINISH

- • Clear — 11, 12, 44, 52, 71
- • Bronze — 22, 33
- ❑ Specify

_____

GLASS STOP

- ❑ With 1" (25 mm) Glass Stops
- ❑ With 1-1/2" (38 mm) Glass Stops

FOR OFFICE USE ONLY

TAKEN BY: _____

PRICED BY: _____

EDITED BY: _____

AVD8848 11.26.18

Custom Series 650-T, 700-T, and 750-T Thermal Door Quote/Order Request Form

NOTE: For quickest lead times and greatest value, specify C.R. Laurence Hardware on all your doors. Visit **crlaurence.com** for Commercial Door Hardware.

THRESHOLD

Clearance from Bottom of Door to Finish Floor

- ❑ Custom
  Specify _____
- ❑ 4-3/4" (120.7 mm)
- ❑ 5" (127 mm) - None (No Allowance)
- ❑ 7" (178 mm)

DOOR CLOSER

- ❑ Surface Mount
- ❑ Drop Plate
- ❑ Door Stop/Holder Degree _____
- ❑ No Closer Required

DOOR SWEEP

- ❑ Yes ❑ No
- ❑ Exposed Fasteners
- ❑ Concealed Fasteners

FRAME SYSTEM

Series IT451 2" x 4-1/2" ❑ Tubular ❑ Open Back
Subframe ❑ 1" x 4-1/2" (Thermal) Tubular Only

FRAME TYPE

- ❑ Up and Over (No Transom)
- ❑ 126" (3.2 m) High With Transom
- ❑ Frame Only
- ❑ Door Only (No Frame)
- ❑ Custom

_____

ADDITIONAL NOTES OR SKETCHES

FOR OFFICE USE ONLY

TAKEN BY: _____

PRICED BY: _____

EDITED BY: _____

APPROVED BY _____ **DATE** _____

AVD8848 11.26.18