Series 375-T Thermal Door Numbering Key

Fax Completed Checklist to U.S. Aluminum Technical Sales at (866) 262-3299. Then call to discuss: (800) 262-5151 (U.S.), (877) 421-6144 (Canada), or (323) 588-1281 (International). Ask for Extension 15305. This form is also available online at **usalum.com**.

Complete Doors include:
Hinging, Pull Handle, Keyed Cylinder, Thumb Turn, Locking Device and 1" Glazing Stops.

SERIES

CODE	DESCRIPTION
AT	Complete Door and Single Point Locking Device for Singles / 3 P.T. Point Locking Device for Pairs / Standard Bottom Rail / Standard Threshold
AZ	Complete Panic Door / Standard Panic / Standard Bottom Rail / Standard Threshold

STILE

CODE	SERIES	DESCRIPTION
4	375-T	Medium Stile

HINGE (Hinging is viewed from exterior.)

CODE	DESCRIPTION
5	1-1/2 Pair Each PBB 4.5 x 4.5 Hinges With Non-Removable Stainless Steel Pins
8	Continuous Geared Hinge Pemko PM SLI

NOTE: Door Frame Exceeding 84" Net Height Requires Additional Hinge.

AT 4 1 5 1 1 R 0

SINGLE/PAIR

CODE	DESCRIPTION
1	Single
2	Pair

FINISH

CODE	DESCRIPTION
11	Clear Anodized
33	Black Anodized
52	Bone White 70% KYNAR® (2 Coat)
71	Standard 70% KYNAR® (2 Coat) Standard Color per Chart _____
71	Custom 70% KYNAR® (2 Coat) - Specify _____
71	Custom 70% KYNAR®(3 Coat) - Specify _____

HANDING

CODE	DESCRIPTION
R	Hinge Right (HR) HRSO
L	Hinge Left (HL) HLSO

SWING

CODE	DESCRIPTION
0	Outswing (SO)

DOOR SWING CHART

AVDB3305 11.26.18